

## MATERIAL SAFETY DATA SHEET

<p>This form may be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. To be valid all information required by 1910.1200(g) of the Standard must appear on this form. Consult the Standard for specific requirements. Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</p>	<p>Quick Name Identifier/Common Name: Liquid Lamp Fuel Blend                  Liquid Paraffin Blend:                  UPC/SKU: L0008 Series, L0010 Series, L0015 Series, L0018 Series, L0019 Series, L0024 Series, L0028 Series, L0029 Series, L0030 Series, L0035 Series, L0036 Series, L0050 Series, L1015 Series, L1018 Series, L1024 Series, L1028 Series, L1029 Series, L1032 Series, L0136 Series, L0224 Series, L0150 Series, L0236 Series, L1036 Series</p>
--	---

### SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<p>Manufacturer's Name:                  Candle Lamp Company                  1815 Rustin Avenue                  Riverside, CA 92507</p>	<p>24 Hour Emergency Telephone Number:                  1-800-255-3924 or 1-813-977-3668 (Collect Calls Accepted)                  Information Telephone Number: 1-951-682-9600</p>
Date Prepared: 1/21/2010	

### SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS No.	% By Weight
C14 – C16 Paraffins	90622-46-1	85-99
White Mineral Oil	8042-47-5	1-15

### SECTION 3 – HAZARDS IDENTIFICATION

Potential Health Effects:	
Eye/Ocular	Irritation may occur with exposure to concentrated vapors or contact.
Skin/Dermal	May cause skin irritation, redness, and scaling upon prolonged contact.
Inhalation	Exposure to high concentration of vapors may result in headache and stupor.
Swallowing/Ingestion	Lung exposure to this product either by prolonged breathing of a mist or vomiting following ingestion, can lead to serious lung injury and possibly death.
Symptoms of Exposure	Symptoms may include headache, dizziness, stupor, or irritation of throat and eyes.
Target Organ Effects	Repeated overexposure to the skin may cause dermatitis.
Developmental Information:	
Cancer Information	Not expected to pose a carcinogenic risk to humans.
Other Health Effects	Pre-existing dermatitis may be aggravated by prolonged skin contact.
Primary Routes of Exposure	Inhalation, ingestion, skin contact, eye contact.

### SECTION 4 – FIRST AID MEASURES

Eyes	Flush eyes gently with water while holding eyelids open for 15 minutes. If symptoms persist or there is any visual difficulty, seek medical attention.
Skin	Remove contaminated clothing. Wash exposed area with soap and water. If irritation continues, seek medical attention. Thoroughly wash contaminated clothes before re-use.
Swallowing	If swallowed, DO NOT induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY.
Inhalation	Move individual away from exposure and into fresh air. If breathing has stopped, perform artificial respiration. GET MEDICAL ATTENTION IMMEDIATELY. Oxygen should only be administered by trained personnel.

<b>SECTION 5 – FIRE FIGHTING MEASURES</b>	
Flash Point	250°F (121°C, Pensky-Martins Closed Cup)
Incompatibility (materials to avoid)	Oxidizers, acids, alkalis.
Explosive Limits	Lower Limit: 0.5%      Upper Limit 7.0%
Auto-ignition Temperature	420°F (216°C)
Hazardous Products of Combustion	May form: carbon dioxide, carbon monoxide and possibly other unidentified organic compounds.
Fire and Explosion Hazard	None expected.
Extinguishing Media	Alcohol compatible foam or water spray, carbon dioxide, dry chemical
Fire Fighting Instructions	Cool exposed equipment with water spray until well after fire is out. Use pressure demand, self-contained breathing apparatus (SCBA) if fighting fires. Individuals should perform only those fire-fighting procedures for which they have been trained.
NFPA Rating: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme	Health – 1, Flammability – 1, Reactivity – 0

<b>SECTION 6 – ACCIDENTAL RELEASE MEASURES</b>	
Spill	Eliminate ignition source, and absorb liquid spill on vermiculite, floor absorbent or other similar absorbent material. Remove to containers for disposal per local, state, and federal ordinances.
Large Spill	Immediately eliminate all ignition sources (open flames, smoking materials, pilot lights, electrical sparks). Remove persons not in appropriate protective gear from area. Stop spill at source. Prevent material from entering drains, sewers and waterways. Prevent spill from spreading. Dike and pump into properly labeled containers for reclamation or removal to containers for disposal per local, state, and federal ordinances. This product is not on the CERCLA Hazardous Substance List.

<b>SECTION 7 – HANDLING AND STORAGE</b>	
Handling	Containers should be handled in well-ventilated areas. Avoid contact with skin and eyes. Keep away from children. Keep away from combustible materials such as paper plates, napkins, etc.
Storage	Containers should be stored away from flame, heat or other ignition sources. Store in a cool dry place (47-120°F, 8-49°C).

<b>SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION</b>	
Ventilation Requirements	Air contaminant levels should be controlled below the PEL or TLV for this product (see Exposure Guidelines below). Mechanical ventilation may be necessary if working with this product in enclosed area and at elevated temperatures.
Eye Protection	Avoid eye contact with material, and wear chemical-resistant goggles.
Skin Protection	Avoid skin contact with material, and wear chemical-resistant gloves.
Respiratory Protection	NIOSH approved respirator for Organic vapors, self-contained breathing apparatus or air-supplied breathing apparatus depending on concentration.
Exposure Guidelines	Manufacturer recommends the ACGIH/OSHA/NIOSH limit of 5 mg/m <sup>3</sup> (8-hour TWA) for exposure to mists of this product. No exposure limit has been set for exposure to vapors of this product.

<b>SECTION 9 – PHYSICAL DATA AND CHEMICAL PROPERTIES</b>	
Appearance and Odor	Clear, oily liquid, mild hydrocarbon odor.
Solubility in Water	Negligible
pH	N/A
Melting Point Range	5.0 °C
Boiling Point range	250 °C to 260 °C
Viscosity	N/A
Vapor Pressure	<0.05 mmHG @ 68 °F (20 °C)
Specific Gravity: Vapor Density	0.7757 @ 60 °F (16 °C, H <sub>2</sub> O = 1): 7 - 8 (Air = 1)

<b>SECTION 10 - STABILITY AND REACTIVITY</b>	
Hazardous Polymerization	Product does not undergo polymerization
Hazardous Decomposition	May form carbon dioxide, carbon monoxide and possibly other unidentified organic compounds.
Chemical Stability	Stable
Incompatibility: Conditions to avoid	Strong oxidizers: Excessive heat, open flames or sparks.

<b>SECTION 11 - TOXICOLOGICAL INFORMATION</b>	
<b>EYES:</b> Eye Irritation Index (Rabbits) 5.7 for non-washed eyes after 1 hour, 6 for washed eyes after 1 hour (Maximum score is 110).	
<b>SKIN:</b> Acute Dermal LD50 (Rabbits) > 2 g/kg. Skin Irritation Index (Rabbits) = 4.4 (Maximum score is 8.0).	
<b>INHALATION:</b> LC50 (Rats) > 5.8 mg/l (nominal) with four hour exposure.	
<b>INGESTION:</b> Acute Oral LD50 (Rat) > 5g/kg.	

<b>SECTION 12 - ECOLOGICAL INFORMATION</b>	
<b>Ecotoxicity:</b> Not available.	
<b>Environmental Fate:</b> Not available.	
<b>Bioaccumulation:</b> Not available.	

<b>SECTION 13 - DISPOSAL INFORMATION</b>	
“Empty” Containers:	Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, sparks, flame, static electricity or other sources of ignition; they may explode and cause injury or death.
Special Instruction:	Contain spill if possible, and pick up using solid adsorbent. Dispose of in accordance with all applicable Federal, State, and local regulations. Note: It is the purchasers’ responsibility to dispose of properly.

<b>SECTION 14 - TRANSPORTATION</b>	
DOT Description:	This product is not a hazardous material according to DOT regulations.
IATA:	Not a dangerous good as defined by IATA for air transportation

<b>SECTION 15 - REGULATORY INFORMATION</b>	
TSCA Inventory Listing:	C14 – C16 Alkanes, CAS Number 90622-46-1.
SARA 302 Components:	None
SARA 313 Components:	None
<b>State and Local Regulations</b>	
California Proposition 65:	None

<b>SECTION 16 - OTHER INFORMATION</b>	
<p>The above data is based on tests and experience, which Candle Lamp Company believes reliable and is supplied for informational purposes only. The Candle Lamp Company’s products are intended for sale to industrial and commercial customers. Candle Lamp Company requests that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Some information presented and conclusions drawn herein may be from sources other than direct test data on the substance itself. Candle Lamp Company disclaims any liability for damage or injury which results from the use of the above data, and nothing contained therein shall constitute a guarantee, warranty (including warranty or merchantability) representation (including freedom from patent liability) by the Candle Lamp Company with respect to data, the product described, or their use for any specific purpose, even if that purpose is known to Candle Lamp Company.</p>	